





# X-RENT

## 6X320W LED - 9M

Our engineers know that the market needs a lighting tower that is rugged, long lasting and safe. The X-START LED has been created beginning from these characteristics. It is the best solution to your needs and guarantees 5400sqm of illuminated area. 11 units can be loaded on a standard truck. To all of this, we added the LED technology that allows for maximum fuel efficiency and reliability.



- 6x320W high efficiency LED floodlight system
- Illuminated area 5400 sqm (5 lux min.)
- On/Off switches - one every two lamps
- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower
- Max height 8.5m
- Hydraulic lifting system
- 340° rotatable mast
- Fully bunded tank, 110%
- Control panel alarms for engine protection and fuel level indicator
- Simple, rugged machine design and layout
- Guided main coiled cable to avoid damage during tower operation
- On board level for guidance during stabilization
- Galvanized metalwork, 80 µm powder coating
- Wind stability up to 80 km/h
- Eye tow hitch-43mm
- Low speed tow trailer single chassis with lights
- 4 height adjustable stabilizers, manual deployment, galvanized steel, leveling system
- Central lifting eye & side forklift pockets
- Very compact dimensions for easy handling

### APPLICATIONS

- Special events
- Rural & hard to reach areas
- Emergency response
- Construction & work sites
- Gas, oil & mining operations
- Military applications



**11**  
Units Per Truck




**You can place 11 units on a single vehicle thanks to one of the compactest footprints on the market.**

KEY BENEFITS

✔ *Easy to move*

✔ *Robustness*

✔ *Versatly*



LIGHT SENSOR  
FEATURED AS STANDARD

SAFETY HYDRAULIC  
VERTICAL MAST

GALVANIZED BODY  
DURABLE ANTI-CORROSION  
PROTECTION

SAFETY AMOSS KIT  
AUTOMATIC MAST  
LOWERING SYSTEM

SIDE FORKLIFT POCKETS

technical data

Dimensions & weight	
Dimensions min. (mm)	2560x1380x2500
Dimensions max. (mm)	2560x2170x8500
Total weight without fuel	1100 Kg


Features	
Rotation	340°
Floodlights	6x320W
Lamps	LED
Options	Homologated axle & towing hitc

Alternator	
Model	Synchronous
Frequency (Hz)	50
Insulation class	H
Degree of protection	IP23
Single phase	8.5Kva
Auxiliary socket	1x16A 240V

Engine	
Model	Kubota D1105
Fuel	Diesel
r.p.m	1500
Tank capacity (l)	115
Consumption (l/h)	1,6
Noise level (dBA) at 7m	68
Running time	71h

Standard load delivery



**11 sets**



Units Per Truck

Illuminated area

**5400 sqm**



**Эксклюзивный официальный дистрибьютор TRIME на территории России и СНГ**

+7 (495) 532-37-34 | +7 (925) 741-89-01  
8 (800) 222-51-05 (Бесплатно для всех регионов)

[www.legion-tehno.ru](http://www.legion-tehno.ru) | [trime@legion-tehno.ru](mailto:trime@legion-tehno.ru)

Компания TRIME оставляет за собой право изменять технические характеристики и товары, описанные в этом каталоге, в любое время и без предварительного уведомления по техническим или коммерческим причинам. Изображения продуктов показаны только